
BLUESTAR 36" RCS SERIES 35 7/8" **• • •** ● ● □ 0 0 1/2" NPT REAR GAS INLET (MUST CONNECT TO NPT GAS SUPPLY LINE) 36 REAR GAS SUPPLY BOX 10 5"-12 2 1/2" (55" CORD DEPTH LOCATION OF GAS CONNECTION A — ISLAND TRIM HEIGHT — 38 1/4" B — 6" STANDARD BACKGUARD HEIGHT — 43 1/4" C — 17" BACKGUARD HEIGHT — 54 1/4" D — HIGH SHELF BACKGUARD HEIGHT — 61" ELECTRICAL CORD LOCATED IN BACK OF UNIT LOCATION OF ELECTRICAL OUTLET MUST NOT BE HIGHER THAN 3" FROM FLOOR IF LOCATED BEHIND THE UNIT OR CAN BE LOCATED IN AN ADJOINING CABINET.

CONFIGURATIONS



RCS366BSS

SPECIFICATIONS:

OVEN INTERIOR: _ _ _ _ _ 29"W x 20"D x 15"H

• SIMMER BURNER RATING $_$ $_$ $_$ $_$ 9,000 BTU, 130°F

• TOP BURNER RATING $_$ $_$ $_$ $_$ $_$ 15,000 BTU

TOP POWER BURNER RATING _ _ _ 18,000 BTU

• INFRARED BROILER RATING _ _ _ _ 15,000 BTU

• OVEN BURNER RATING $_$ $_$ $_$ $_$ $_$ 30,000 BTU

ELECTRICAL REQUIREMENTS _ _ _ 120V, 60Hz, 15 AMPS, 1 PH
(UNIT MUST BE ON A NON-GFI, DEDICATED OUTLET)

OPERATING GAS PRESSURE _ _ _ NAT: 5.0" WC

LP: 10.0" WC

• INSTALLATION CLEARANCE _ _ _ _ 0" SIDE CABINET 0" BACK WALL

OPTIONS

CASTERS

· ADDITIONAL OVEN RACK

· FULL EXTENSION OVEN RACK

VISIT www.bluestarcooking.com FOR CUSTOM CONFIGURATIONS

File: 2011_RCS36.dwg

