

With its distinctive combination of commercial-style performance and unrivaled customization options, the BlueStar® Nova Series offers unique options tailored to any individual style or cooking preference. Available in 1,000+ colors and multiple metal trim finishes, the Nova Series can be customized with integrated cooking features like griddles, charbroilers, and swing doors.

PRODUCT FEATURES

- 22,000 UltraNova™ open burners
- Gentle 130° simmer burner
- Integrated wok cooking - no wok ring needed
- Extra-large convection oven with 1850° infrared broiler that can accommodate an 18" x 26" baking sheet
- Includes full extension oven rack plus two standard racks
- Available in 1,000+ colors & multiple trim options
- Available with swing doors
- Handcrafted in Pennsylvania since 1880
- Available in Natural or LP gas

SPECIFICATIONS

Range Dimensions: 48.875"W x 24"D x 36.75"H
 Large Oven Interior: 26.438"W x 20"D x 15"H
 Small Oven Interior: 13.578"W x 20"D x 15"H
 Top Burner Rating: 22,000 BTUs
 Simmer Burner Rating: 1,300 BTUs
 24" French Top Rating: 18,000 BTUs
 Large Oven Burner Rating: 30,000 BTUs
 Small Oven Burner Rating: 15,000 BTUs
 Infrared Broiler Rating: 15,000 BTUs
 Electrical Requirements: 120V, 60Hz, 15 AMPs, 1 PH
 (Unit must be on a Non-GFI, dedicated outlet)
 Operating Gas Pressure: NAT: 5.0" WC, LP: 10.0" WC
 Gas Line Size: 3/4"
 Installation Clearance: 0" Side Cabinet, 0" Back Wall




MODEL CONFIGURATION

Four Burners
with 24" French Top

RNB486FTV2


BURNER CONFIGURATION




ADDITIONAL CUSTOMIZATION OPTIONS

- 1,000+ Colors & finishes
- 190 Knob colors
- Multiple trim options
- Swing doors
- Backguards

*All specifications subject to change without notice.
 Visit www.bluestarcooking.com for most up to date
 information prior to installation or site preparation.*




Electrical cord located in back of unit.
Location of electrical outlet must not be higher than 4" from floor if located behind the unit or can be located in an adjoining cabinet.



- (A) Island Trim Height - 37 1/2"
- (B) 6" Standard Backguard Height - 43"
- (C) High Shelf Backguard Height - 60 3/4"

RELATED PRODUCTS

VENTILATION



CLEARANCES