

Introducing the new BlueStar® Built-in French Door Refrigerator/Freezer. Featuring commercial-style design and performance, our Refrigeration line offers advanced food preservation capabilities, unique features for the discerning home chef and unmatched customization options.



### PRODUCT FEATURES

- Dual compressors and evaporators for extended food preservation
- Oversized Capacity: 22.2 cu ft
- Full extension tray that fits commercial size sheet pans
- Ramp-on LED lighting
- Extra-large, fully extending drawers with soft-close technology
- Professional-grade glass & metal shelves/bins
- Adjustable and removable shelves and bins
- Automatic ice maker with Max Ice option
- Over-sized freezer that fits commercial-size sheet pan
- Precise OLED touch screen controls
- Unmatched customization: choose from 750+ colors and finishes and 9 metal trims

### SPECIFICATIONS

Dimensions: 35 3/4"W x 26 3/16"D x 83 1/8"H  
Electrical Requirements: 115V, 60Hz, 15 AMP circuit  
(Unit must be on a Non-GFI, dedicated outlet)  
Water Pressure: 35-120psi

### MODEL CONFIGURATIONS

36" French Door Refrigerator/Freezer      BBBF361



## Refrigerator Dimensions:

- 83 1/8" high
- 35 3/4" width
- 26 3/16" depth

## Cut-out Dimensions (Standard Built-in Installation):

- 83 1/4" - 84" high
- 35 1/2" width
- 24" depth

The doors will extend beyond the front of the enclosure by 2 3/8"



## Site Preparation Guide:

### Electrical:

The electrical outlet should be located in the area marked "Electrical" in Fig 2 and must be on a separate 115VAC, 60Hz, 15 amp circuit and accept a three-prong grounding plug.

The outlet may also be located above the enclosure. However, an access hole would need to be created in the back left corner of the top of the enclosure to route the power cord.

### Plumbing:

The water line should be located in the area marked "Water" in Fig 2. If it is outside this area, it may be damaged during installation and prevent the refrigerator from being installed at the proper depth. It must use 1/4" OD copper, braided stainless steel, or PEX tubing and have 36" of excess line. The water pressure must be between 35-120 psi.

**Important:** The water line cannot be exposed to temperatures below freezing.

Connect the water line to the house water supply with an easily accessible shut-off valve, not a self-piercing valve. Purge the water line before connecting it to the refrigerator. This will remove any debris that might be present.

