

Featuring commercial-style design and performance, our PRO Built-In Refrigeration line offers advanced food preservation capabilities, unique features for the discerning home chef and unmatched customization options.

PRODUCT FEATURES

- Dual compressors and evaporators for extended food preservation
- Durable 304-grade stainless steel interiors
- Extra-large capacity: 22.4 cu ft
 - Refrigerator 16.66 cu ft
 - Freezer 5.73 cu ft
- Professional-grade glass & metal shelves and bins
- Ramp-on LED lighting
- Precise touch screen controls
- Full extension tray that fits commercial size sheet pans
- Extra-large, fully extending drawers with soft-close technology
- Adjustable and removable shelves and bins
- Automatic ice maker with Max Ice option
- Over-sized freezer that accommodates commercial size sheet tray
- Energy Star Certified
- Designed and manufactured in the USA
- Unmatched customization - choose from 1,000+ colors and 10 metal trim finishes

SPECIFICATIONS

Dimensions: 35 3/4"W x 26 3/16"D x 83 1/8"H

Electrical Requirements: 115V, 60Hz, 15 AMP circuit

(Unit must be on a Non-GFI, dedicated outlet)

Water Pressure: 35 - 120psi

Unit Capacity: 22.4 cu ft



MODEL NUMBERS

Right Hinge / Left Handle	BBB36R3
Left Hinge / Right Handle	BBB36L3



Model Shown: BBB36R3



Model Shown: BBB36R3C



Refrigerator Dimensions:

Height: 83 1/8"
Width: 35 3/4"
Depth: 26 3/16"

Cut-out Dimensions (Standard Built-In Installation):

Height: 83 1/4" - 84"
Width: 35 1/2"
Depth: 24"

Note: The doors will extend beyond the front of the enclosure by 2 3/8"

For additional installation options, check the detailed installation dimensions at www.bluestarcooking.com



Site Preparation Guide:

Electrical:

The electrical outlet should be located in the area marked "Electrical" in Fig 2 and must be on a separate 115VAC, 60Hz, 15 amp circuit and accept a three-prong grounding plug.

The outlet may also be located above the enclosure. However, an access hole would need to be created in the back left corner of the top of the enclosure to route the power cord.

Plumbing:

The water line should be located in the area marked "Water" in Fig 2. If it is outside this area, it may be damaged during installation and prevent the refrigerator from being installed at the proper depth. It must use 1/4" OD copper, braided stainless steel or PEX tubing and have 36" of excess line. The water pressure must be between 35 - 120psi.

Important: The water line cannot be exposed to temperatures below freezing.

Connect the water line to the house water supply with an easily accessible shut off valve, not a self-piercing valve. Purge the water line before connecting it to the refrigerator. This will remove any debris that might be present.

